



DIAGONAL BAR DETAILS

NOTES

1. APPLICABLE TO SLIP FORM CONSTRUCTION METHOD ONLY.
2. REFER TO STANDARDS FOR SPACING OF VERTICAL AND HORIZONTAL REINFORCEMENT.
3. DIAGONAL NO. 4 BARS SHALL BE ASTM A 615, GRADE 60.
4. ALL REINFORCEMENT BARS, INCLUDING ENDS AND TIES, SHALL BE EPOXY COATED.

SPECIFICATION 604	CATEGORY CODE ITEMS	<div>Maryland Department of Transportation</div> <div>STATE HIGHWAY ADMINISTRATION</div> <div>STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES</div> <div>DIAGONAL BAR FOR ALL SLIP FORMED</div> <div>F SHAPE DOUBLE FACED CONCRETE</div> <div>MEDIAN TRAFFIC BARRIER</div>	
APPROVED	<div>Kirk G. McCall</div> <div>DIRECTOR - OFFICE OF HIGHWAY DEVELOPMENT</div>		
<div>SHA</div> <div>State Highway Administration</div>	APPROVAL • SHA REVISIONS	APPROVAL • FEDERAL HIGHWAY ADMINISTRATION	
	APPROVAL 3-1-01	APPROVAL 3-28-01	
	REVISED 2-10-04	REVISED 3-31-04	
	REVISED	REVISED	
	REVISED	REVISED	
		STANDARD NO. MD 648.44-04	